

## B4 BR Mk1 CORRIDOR BRAKE FIRST (BFK)

D161

28 built 1960-1964; withdrawn 1972-2009; 13 preserved or in railtour use 64'6"

These etched sides can be built into a complete coach using products from our range as supplied in our full kits; please refer to the panel opposite. They can also be used as a basis for a scratchbuilt coach, or to overlay a suitable RTR model.

One of the last Mk1 types to be introduced. Initially, they would have seen service on important expresses, being marshalled at the first class end of the train, i.e. closest to the buffer stops for departures from London termini, or behind the tender on up trains.

### Running numbers and original regional allocations

W14000-1	built 1960	BR Ashford/Swindon	B1 bogies
M14002-12	built 1960/1	BR Ashford/Swindon	B1 bogies
M14013-22	built 1961/2	BR Swindon	Commonwealth bogies
M14023-27	built 1994	BR Swindon	Commonwealth bogies

### Livery

From 1956 to 1964 most coach types were painted maroon with gangwayed stock lined gold/black/gold at the waist and black/gold above the windows. This later livery saw the introduction of a new circular crest, which appeared with increasing frequency from around 1959. From 1965 onwards, where spray painting of the coaches was done, the ends were painted body colour to avoid the need for masking. Also from 1965 the new 'corporate image' livery of blue and grey was introduced. The grey was not carried to the end of the coach and there was a white line between it and the blue. Lettering and insignia were white. With the introduction of sectors, coaches appeared in many new liveries, too many to describe here.

### Underframe building tips

1. The stepboards are best fitted after the solebars are soldered to the chassis but before the headstocks are soldered on and the central trussing is folded down. Use thin card to pack the stepboards up from the bottom of the solebar.
2. Solder a piece of scrap brass above the vacuum cylinder, spanning from the side to the centre strip. This gives a flat surface to solder the cylinder to.
3. The inner and outer frames of the regulator box cradle should be parallel. To fit the regulator box, place the underframe upside down and hold the box in place using a small flat file whilst fixing it in position.
4. Fit the dynamo by wedging the inner edge of the base in the angle formed by the upper and lower members of the centre trussing.
5. Leave a length of sprue attached to each direct admission valve which will span the centre truss from top to bottom. Hold the valve in position with a small flat file whilst fixing, and trim away the excess sprue afterwards.

### Further information


British Railways Mk1 Coaches (and Supplement)	Keith Parkin	HMRS
BR Mark 1 & Mark 2 Coaching Stock	Hugh Longworth	OPC

COMET MODELS components required to complete this carriage are:

Underframe	UB1	Bogies	BB1 or BB2
Underframe castings	UCB1	Interior	INT1
Ends	EB1	End castings	ECB1
Roof	C10	Roof castings	RC3
Periscopes	C16		


### Scrap views showing additional detailing of sides and ends

(not all details may apply to this diagram)




1. Window insignia (Firsts and No Smoking. In RH quarterlights of non-gangwayed stock)
2. Destination board bracket
3. Door insignia (First only and only on passenger doors)
4. Grab handles
5. Door hinges
6. Number (RH end 6" below waistline)
7. Slate grey panel on luggage doors
8. Door insignia (Guard and Kitchen on non-passenger doors)
9. Stepboards
10. Vehicle description, e.g. Kitchen Car (6" below waistline and central on side)

End A






End B




ROOF AND INTERIOR PLANS  
VIEWED FROM ABOVE

Train alarm gear this end



UNDERFRAME VIEWED  
FROM BELOW



- 1. Dynamo
- 2. Direct admission valve
- 3. Vacuum cylinder
- 4. Lamp resistance box
- 5. Regulator
- 6. Battery box
- 7. Distribution fuse box
- 8. Stepboard
- 9. Guard's ascending step